



AURORA

FIXED SPEED







AURORAFIXED SPEED

Code			22022010007977
Factory Indoor Cod	e		22022011008470
Factory Indoor Code			22022011009858
Factory Outdoor Code			22022016008432
Factory Outdoor Code			22022016009639
Model			MSABF-34HRN1-QC2V
Indoor			MSABF-34HRN1-QC2V
Indoor			MS12F-36HRFN1-QC2GV
Outdoor			MOD30-34HN1-QC2W
Outdoor			MOD80U-36HRFN1-QC2GV
Power supply		V-Hz-Ph	220-240V~ 50Hz, 1Ph
	Capacity	W	9965
Cooling	Input	W	3120
	Rated current	Α	14,50
	EER	W/W	3,19
	Capacity	W	10844
Heating	Input	W	3080
	Rated current	Α	14,3
	COP	W/W	3,52
Max. input consump		W	3978
Max. current		A	17,8
Starting current		A	
Starting current		A	/ AT0000\/4\\PAT
Compressor	Model		ATQ390V1UMT
	Туре		ROTARY
	Brand		GMCC
	Capacity	Btu/h	33990
	Input	W	3272
	Rated current(RLA)	Α	15,1
	Locked rotor Amp(LRA)	Α	1
	Thermal protector		1
	Thermal protector position		INTERNAL
	Capacitor	uF	70
	Refrigerant oil/oil charge	ml	1100 CC (VG74)
	Model		YKFG-60-4-2
Indoor fan motor	Input	w	100
		- 11	
	Capacitor	uF	3.5
	Speed((turbo)/Hi/Mi/Lo)	r/min	1210/1080/900
Indoor coil	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7.innergroove tube
			-
	f.Coil length x height x width	mm	965x378x40.11
	g.Number of circuits		7
Indoor air flow((turbo	o)/Hi/Mi/Lo)	m3/h	1370/1200/980
Indoor noise level((t	urbo)/Hi/Mi/Lo)	dB(A)	50.8/47.1/41.7
Indoor unit	Dimension(W*D*H)	mm	1259x282x362
	Packing (W*D*H)	mm	1340x450x380
	Net/Gross weight	Kg	21.8/27.6
	Model		YKT-60-6-40
Outdoor fan motor	Input	W	133/125
	Capacitor	uF	5
	Speed (HI)	r/min	870/-/820
	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
Outdoor coil	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	1005x756x40.11
	g.Number of circuits		6
Outdoor noise level		dB(A)	62,1
Outdoor unit	Dimension(W*D*H)	mm	946x420x810
	Packing (W*D*H)	mm	1090x500x875
	Net/Gross weight	Kg	70/75
Refrigerant type		g	R410A/2650
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ф9.52/Ф15.9(3/8"/5/8")
	Max. refrigerant pipe length	m	25
	Max. difference in level	m	10
Connection wiring		- 111	4x1.0(Optional)
			4x1.0(Optional)
Plug type			
Thermostat type			Remote Control
ingration temperati		°C	17-30
Operation temperati		00	17-32/0-30
	Indoor(cooling/ heating)	℃	
Room temperature	Indoor(cooling/ heating) Outdoor(cooling/heating)	°C	18-43/-7-24



